549, 280

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau

(43) International Publication Date
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number
WO 2004/088235 A1

(51) International Patent Classification[7]: F28G 9/00 // F28F 19/01, F23J 3/00, G06F 19/00

(21) International Application Number: PCT/FI2004/000190

(22) International Filing Date: 31 March 2004 (31.03.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/458,442 31 March 2003 (31.03.2003) US

(71) Applicant *(for all designated States except US)*: **TR-TECH INT. OY** [FI/FI]; Linnankatu 64 A, FI-20100 Turku (FI).

(72) Inventor; and

(75) Inventor/Applicant *(for US only)*: **ROSIN, Tomas** [FI/FI]; Läntinen Rantakatu 65 C 31, FI-20100 Turku (FI).

(74) Agent: **TURUN PATENTTITOIMISTO OY**; P.O. Box 99, FI-20521 Turku (FI).

(81) Designated States *(unless otherwise indicated, for every kind of national protection available)*: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States *(unless otherwise indicated, for every kind of regional protection available)*: ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: METHOD AND SYSTEM IN A HEAT EXCHANGE SYSTEM AND METHODS FOR AIR/FUEL CONTROL AND FOR SOOT CLEANING OPTIMIZATION



(57) Abstract: Means for obtaining accurate knowledge of location and amount of fouling inside a heat exchange system, such as a boiler of a power plant, are provided. According to the invention this knowledge can be used to optimize cleaning of a heat exchange system. The system of the invention comprises: Means for measuring particles in the exhaust gas stream of the heat exchange system. These particles are at least partly released when cleaning a certain part of the heat exchange surface of the heat exchange system. Means for creating information of the fouling in an electronic memory by linking together coordinates of the part of the heat exchange surface being cleaned and the measurement data created during the cleaning of said part.

WO 2004/088235 A1

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.